



Product Service

Attestation of Conformity

No. N8A 18 04 90712 008

Holder of Certificate: Zhongshan SECOCO Optoelectronic Technology CO., Ltd.

No.3 Futian Five Road, Shite Industrial Park, Gangkou Town
528447 Zhongshan City, Guangdong Province
PEOPLE'S REPUBLIC OF CHINA

Product: Power supplies
(Dimming LED Driver)

Model(s): SK401-B-06xxx; SK401-B-07xxx; SK401-B-10xxx;
SK401-B-11xxx; SK401-B-12xxx; SK401-B-13xxx;
SK401-B-14xxx
[“xxx” =200-450, 500-700, indicates rated output current
(Irated) 200-450mA, 500-700mA, in steps of 5mA]


Parameters:

Rated Input Voltage :	200-240VAC
Rated Frequency :	50/60Hz
Rated Input Current :	0.1A
Rated Output :	See page 2 for details
Protection against Electric Shock :	Class II; SELV
Degree of Protection :	IP20
Method of Installation:	Independent
Type of Output :	Constant current type
ta; tc :	ta:50°C; tc:85°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015
EN 62493:2015

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 651401703501


(Taylor Yao)

Date, 2018-04-23



CE After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity No. N8A 18 04 90712 008

Model	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W) max.
SK401-B-06xxx	9-20	200-350	27	7.0
SK401-B-07xxx	12-24	200-300	32	7.2
SK401-B-10xxx	18-30	200-400	37	12.0
SK401-B-11xxx	15-24	300-450	32	10.8
SK401-B-12xxx	9-16	500-700	23	11.2
SK401-B-13xxx	25-40	200-300	49	12.0
SK401-B-14xxx	25-40	250-350	49	14.0

Remark:

“xxx” =200-450, 500-700, indicates rated output current (I_{rated}) 200-450mA, 500-700mA, in steps of 5mA