

## ATTESTATION OF CONFORMITY

No.: 23662412AA01

With respect to Directive 2014/30/EU Electromagnetic Compatibility, Telab declares that  
the equipment:

Product Description: **Cable Reel**

Trademark: **Znpon**

Model: **MPR-H, MPR-HB, MPR-U, MPR-P, MPR-H-P, MPR-U-P, MPR-P-P,  
MPR-H-D, MPR-U-D, MPR-P-D, MPR-H-F, MPR-U-F, MPR-P-F**

Parameters: **See Appendix**

Manufacturer: **Ningbo Znpon Electrical Appliance Co., Ltd.**

Address: **No.1018 Tianyuan Avenue, Zhouxiang Town, Cixi, Ningbo City,  
Zhejiang Province, China**

This statement is granted to:

Name: **Ningbo Znpon Electrical Appliance Co., Ltd.**

Address: **No.1018 Tianyuan Avenue, Zhouxiang Town, Cixi, Ningbo City,  
Zhejiang Province, China**

Applied specifications/standards: **EN 55032:2015+A1:2020+A11:2020, EN 55035:2017+A11:2020  
EN IEC 55015:2019+A11:2020, EN IEC 61000-3-2:2019+A1:2021  
EN 61000-3-3:2013+A1:2019+A2:2021**


Report No.: **20230233ER**

Date: **April 13, 2023**



Van Lantinge  
Manager Certification

An "EC Declaration of Conformity" issued by the manufacturer, and application of the CE Mark, is permitted after all applicable requirements are met in accordance with European Union Rules.





## ATTESTATION OF CONFORMITY

NO.: 23662412AA01

### (APPENDIX)

Type	Max Rated Power Full-reeled/unreeled	Cord Information	Remark
MPR-H, MPR-H-P, MPR-H-D, MPR-H-F	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled) USB input: 100-250V~ USB output: 5VDC 1.6A(with light on) 5VDC 2.1A(with light off) LED light: Max 5V 1.5W	H05VV-F 3G1.5 mm <sup>2</sup> 15m/20m; H07RN-F 3G1.5 mm <sup>2</sup> 15m	Plastic enclosure, a plug industrial, 3 way household socket-outlets, with a RCCB, with a breaker, IP44.
MPR-HB	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled) USB input: 100-250V~ USB output: 5VDC 1.6A(with light on) 5VDC 2.1A(with light off) LED light: Max 5V 1.5W Lithium battery:3.7V 2600MAh	H05VV-F 3G1.5 mm <sup>2</sup> 15m/20m; H07RN-F 3G1.5 mm <sup>2</sup> 15m	
MPR-U, MPR-U-P, MPR-U-D, MPR-U-F	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled) USB input: 100-250V~ USB output: 5VDC 1.6A(with light on) 5VDC 2.1A(with light off)	H05VV-F 3G1.5 mm <sup>2</sup> 15m/20m; H07RN-F 3G1.5 mm <sup>2</sup> 15m	
MPR-P, MPR-P-P, MPR-P-D, MPR-P-F	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled)	H05VV-F 3G1.5 mm <sup>2</sup> 15m/20m; H07RN-F 3G1.5 mm <sup>2</sup> 15m	

Directive: 2014/30/EU  
Report No.: 20230233ER



Van Lantinge  
Manager Certification

An "EC Declaration of Conformity" issued by the manufacturer, and application of the CE Mark, is permitted after all applicable requirements are met in accordance with European Union Rules.

