

ATTESTATION OF CONFORMITY

No.: 23662412AA02

With respect to Directive 2014/35/EU Low Voltage, Telab declares that the equipment:

Product Description: **Cable Reel**

Trademark: **Znpon**

Model: **MPR-H, MPR-HB, MPR-U, MPR-P, MPR-H-P, MPR-U-P, MPR-P-P,
MPR-H-D, MPR-U-D, MPR-P-D, MPR-H-F, MPR-U-F, MPR-P-F**

Parameters: **See Appendix**

Manufacturer: **Ningbo Znpon Electrical Appliance Co., Ltd.**

Address: **No.1018 Tianyuan Avenue, Zhouxiang Town, Cixi, Ningbo City,
Zhejiang Province, China**

This statement is granted to:

Name: **Ningbo Znpon Electrical Appliance Co., Ltd.**

Address: **No.1018 Tianyuan Avenue, Zhouxiang Town, Cixi, Ningbo City,
Zhejiang Province, China**

Applied specifications/standards: **EN 61242:1997+A1:2008+A2:2016+A13:2017
EN 60598-1:2015+A1:2018, EN 60598-2-4:2018
EN 62368-1:2014+A11:2017, EN 62233:2008**

Report No.: **20230233EL**

Date: **April 13, 2023**



Van Lantinge
Manager Certification

An "EC Declaration of Conformity" issued by the manufacturer, and application of the CE Mark, is permitted after all applicable requirements are met in accordance with European Union Rules.



ATTESTATION OF CONFORMITY

NO.: 23662412AA02

(APPENDIX)

Type	Max Rated Power Full-reeled/unreeled	Cord Information	Remark
MPR-H, MPR-H-P, MPR-H-D, MPR-H-F	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled) USB input: 100-250V~ USB output: 5VDC 1.6A(with light on) 5VDC 2.1A(with light off) LED light: Max 5V 1.5W	H05VV-F 3G1.5 mm ² 15m/20m; H07RN-F 3G1.5 mm ² 15m	Plastic enclosure, a plug industrial, 3 way household socket-outlets, with a RCCB, with a breaker, IP44.
MPR-HB	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled) USB input: 100-250V~ USB output: 5VDC 1.6A(with light on) 5VDC 2.1A(with light off) LED light: Max 5V 1.5W Lithium battery:3.7V 2600MAh	H05VV-F 3G1.5 mm ² 15m/20m; H07RN-F 3G1.5 mm ² 15m	
MPR-U, MPR-U-P, MPR-U-D, MPR-U-F	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled) USB input: 100-250V~ USB output: 5VDC 1.6A(with light on) 5VDC 2.1A(with light off)	H05VV-F 3G1.5 mm ² 15m/20m; H07RN-F 3G1.5 mm ² 15m	
MPR-P, MPR-P-P, MPR-P-D, MPR-P-F	Max:10A 250V~ 2500W(cable fully extended) 1000W(cable fully reeled)	H05VV-F 3G1.5 mm ² 15m/20m; H07RN-F 3G1.5 mm ² 15m	

Directive: 2014/35/EU
Report No.: 20230233EL



Van Lantinge
Manager Certification

An "EC Declaration of Conformity" issued by the manufacturer, and application of the CE Mark, is permitted after all applicable requirements are met in accordance with European Union Rules

