

TEST REPORT

Report Number : HA0124NB040809SPS

Applicant's name : NINGBO DIE CASTING MAN ENERGY CO., LTD.

Applicant's address : Dajiahe Industrial Zone, Ninghai town, Ningbo City, China

Name of manufacturer : NINGBO DIE CASTING MAN ENERGY CO., LTD.

Address of manufacturer : Dajiahe Industrial Zone, Ninghai town, Ningbo City, China

Name of factory (ies) : NINGBO DIE CASTING MAN ENERGY CO., LTD.

Address of factory (ies) : Dajiahe Industrial Zone, Ninghai town, Ningbo City, China

Product Name : LED Street light

Trade Mark(s) : N/A

Model No. : YASL-27-120M, YASL-27-40, YASL-27-60, YASL-27-200,
YASL-27-40M, YASL-27-60M, YASL-27-120M, YASL-27-200M,
YASL-27H-120, YASL-27H-200, YASL-27H-120M,
YASL-27H-200M,

Ratings : 100-240V~, 50/60Hz, IP66

Total number of pages : 9 pages

Standard : EN 60529:1991 + A1:2000 + A2:2013
IEC 60529:1989 + A1:1999 + A2:2013

Date of Receipt sample : April 11, 2024

Date of Test : April 11, 2024 to April 16, 2024

Date of issue : April 30, 2024

Test Report Form No. : HATEK60529_IP66A

Test Result : Pass

Prepared By:

Ningbo HATEK Co., Ltd.

6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: +86-574-87171888

E-mail: info@hatek.com.cn

Prepared by:

Rick Chen

Rick Chen / Project Engineer

Approved by:

Milse Xie

Milse Xie / General Manager



TEST REPORT

General product information:

1. The products covered in this report are only LED street lights.
2. All models are the same except for size.
3. The model YASL-27-120M was selected to conduct full tests.

This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT

List of test items:

Test Model	Test Items	Result
1	IP6X test	Pass
2	IPX6 test	Pass

This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT

Test Items:

- 1) Test for protection against access to hazardous parts: IP6X
- 2) Test for protection against solid foreign objects: IP6X

Test Method:

The tests should be carried out under the standard atmospheric condition.

The atmospheric conditions during tests are as follows:

Temperature range: 15°C to 35°C.

Relative humidity: 25% to 75%.

- 1) Wire of 1.0mm Φ is inserted through any openings of the enclosure with a force of $1N \pm 10\%$.
- 2) The enclosure under test is supported inside the test chamber and the pressure inside the enclosure is maintained below the surrounding atmospheric pressure by a vacuum pump.
A volume of air 80 times the volume of the sample enclosure tested without exceeding the extraction rate of 60 volumes per hour. In no event shall the depression exceed 2kPa.
If an extraction rate of 40 to 60 volumes per hour is obtained the duration of the test is 2h.
If, with a maximum depression of 2kPa, the extraction rate is less than 40 volumes per hour, the test is continued until 80 volumes have been drawn through, or a period of 8h has elapsed.

Acceptance Conditions:

- 1) The protection is satisfactory if adequate clearance is kept between the access probe and hazardous parts.
- 2) The protection is satisfactory if no deposit of dust is observable inside the enclosure at the end of the test.

Test Result:

- 1) Adequate clearance was kept between the test wire and hazardous parts.
- 2) No deposit of dust is observable inside the enclosure.

☒ Pass ☐ Fail



This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT



This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT

Test Item:

Tests for protected against water jets: IPX6

Test Method:

Internal diameter of the nozzle: 12.5mm;

Delivery rate: 100L/min $\pm$ 5%;

Water pressure: to be adjusted to achieve the specified delivery rate;

Core of the substantial stream: circle of approximately 120mm diameter at 2.5m distance from nozzle;

Test duration per square meter of enclosure surface area likely to be sprayed: 1min;

Minimum test duration: 3min;

Distance from nozzle to enclosure surface: between 2.5m and 3m.

Acceptance Conditions:


In general, if any water has entered, it shall not:

- be sufficient to interfere with the correct operation of the equipment or impair safety;
- reach live parts or windings not designed to operate when wet;
- accumulate near the cable end or enter the cable if any.

Test Result:

There was water accumulating on the inner wall of the enclosure.

☒ Pass ☐ Fail



Dimensions in millimetres

$D' = 6,3$ for the test of 14.2.5 (second characteristic numeral 5)

$D' = 12,5$ for the test of 14.2.6 (second characteristic numeral 6)

This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT

Photos:

Before the test (YASL-27-120M)



This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China


Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT

During the test IP6X



After the test IP6X



This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China


Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn

TEST REPORT

During the test IPX6



After the test IPX6



====End of Test Report ====

This document cannot be reproduced except in full, without prior written approval of HATEK. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Ningbo HATEK Co., Ltd.

Address: 6F, No. 65, Mujin Road, National Hi-Tech Zone, Ningbo, Zhejiang 315013, China

Tel: 86-574-87171888 www.hatek.com.cn E-mail: info@hatek.com.cn