





Test Report SL52115283820301TX Date:July 16,2021

Page 1 of 10

1/F 266-270, TEXACO ROAD, TSUEN WAN, N.T., HONG KONG

THIS REPORT CANCELS AND SUPERSEDES THE TEST REPORT NO.SL52045325382401TX DATE: 2020-12-24 AND NO.SL52035298282101TX DATE: 2020-09-29 ISSUED BY SGS (Shanghai) UPDATED CLIENT INFORMATION/ SAMPLE INFORMATION.

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description (A)Face mask

Sample Color (A)WHITE

Composition (A)Polypropylene

3D3PH Style No.

Manufacturer SAVEWO LIMITED

Test Performed Selected test(s) as requested by applicant

Sample Receiving Date Sep 15, 2020

Testing Period Sep 17, 2020 - Sep 29, 2020

Test Result(s) Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Sample No. **Recommendation Level** FFP2 NR

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center

Sara Guo (Account Executive)



mile adoctiment is issued by the Company stoplest to its Gentral Conditions, in the Company stoplest to its Gentral Conditions of the Company stoplest to its Gentral Conditions of the Company in Com

3"Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 f (86-21) 64958763



SL52115283820301TX

Date:July 16,2021

Page 2 of 10

Test Result

# Personal Protective Equipment - Respiratory Protective Devices- Filtering Half Masks to Protect against Particles- Requirements, Testing, Marking

EN 149:2001+A1:2009

#### Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination	Comply	Pass
before use.		

#### Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	Comply	
After undergoing the conditioning described in 8.3.1 none of the particle		
filtering half masks shall have suffered mechanical failure of the facepiece	Comply	FOFF
or straps. L V (ARL) LL V (ARL) LL	- V ( AL	Pass
When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering	Committee	
half mask shall not collapse.	Comply	ette
Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.	Comply	

#### Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer.  With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Not applicable (Not designed to be re-usable)	N.A.

#### Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard	No imperfections	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents as <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms



SL52115283820301TX

Date:July 16,2021

Page 3 of 10

#### Clause 7.8 Finish of Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer shall have no sharp edges or burrs.	No sharp edges or burrs	Pass

### Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009, Clause 8.5)

Test Requirement	Results	Comment
The total inward leakage consists of three components: face seal leakage, exhalation valve leakage (if exhalation valve fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3	Detail refer to Appendix 1	Meet FFP1, Meet FFP2
and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3		

# Appendix 1: Summarization of Test Data

Inward Leakage Test Data

IIIWara Ecakage Test Bata									
Subject	Sample No.	Condition	Walk(%)	Head Side/side(%)	Head up/down(%)	Talk(%)	Walk(%)	Mean(%)	
Zhou		A.R.	5.53	5.67	6.04	7.70	5.56	6.10	
Luo	2	A.R.	7.05	7.32	7.40	7.09	6.92	7.16	
Lu	3	A.R.	6.06	4.64	6.64	5.38	7.32	6.01	
Wang	4	A.R.	4.59	5.25	5.05	5.79	4.94	5.12	
Bao	5	A.R.	6.77	6.88	6.79	7.59	7.61	7.13	
Ding	6	T.C.	5.59	5.08	5.05	5.45	5.30	5.29	
Li	7	T.C.	6.27	5.37	7.51	6.92	7.02	6.62	
Chen	8	T.C.	5.70	5.26	6.55	6.08	4.64	5.65	
Song	9	T.C.	7.29	5.89	5.85	6.69	6.26	6.40	
Ye	10	T.C.	8.36	6.60	7.22	6.83	6.67	7.14	

#### Facial Dimension(mm)

Subject	Face length	Face Width	Face Depth	Mouth Width
Chen	125	150	120	58
Lu	115	132	107	48
Zhou	115	135	106	52
Li	125	130	107	46
Luo	125	136	100	43
Zheng	128	140	112	55
Wang	120	147	103	48



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.gs.com/en/Terms-and-Conditions.aspx.and">http://www.gs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents as <a href="http://www.gs.com/en/Terms-and-Conditions.aspx.and">http://www.gs.com/en/Terms-and-Conditions.aspx.and</a>, Attention is drawn to the imitation of liability, indemnification and jurisdiction issues defined therein. Any holder of his document is a fitting that the service of the servi

or small: C.N. Deccheck@sas.com 1<sup>3</sup> Building.No.893/tehan Road.Xuhu District Stranghai.China 200233 t (86-21) 61402666 f (86-21) 64958763 www.sgsgroup.com.cn 中国 - 上海 - 終正区宜山路889号3号楼 邮票:200233 t (86-21) 61402666 f (86-21) 64958763 e sgs.china@sgs.com



Test Report SL521		115283820301TX	Date:July 16,2021	Page 4 of 10
Song	120	140	100	50
Bao	130	134	104	50
Ding	134	150	110	52
Liu	120	135	117	50
Ye	126	137	105	52

#### Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

		Test Requirement		Results	Comment	
The	penetration	of the filter of the particle filteri	ng half mask shall meet the	е		
requ	irements of	the following table.				
	Classifica	Maximum penetration	on of test aerosol			
	tion	Sodium chloride test 95	Paraffin oil test 95 l/min			
		l/min			Detail refer to	Meet FFP1,
		%	%		Appendix 2	Meet FFP2
		max.	max.			
	FFP1	20	20			
	FFP2	6	6			
	FFP3	1	1			

# Appendix 2: Summarization of Test Data

#### Penetration of filter material

Aerosol	$\bigcap A \bigcap \Gamma$ Condition $\bigvee \bigcap A$	Sample No.	Penetration [ ]			
ILLULL V	CHILLDEL V CH		0.564			
	As received	2	0.573			
		3	0.626			
		4	0.569			
Sodium chloride test	Simulated wearing treatment	5	0.538			
		6	0.591			
	Mechanical strength +Temperature conditioned	7	1.809			
		8	1.703			
	conditioned	9	1.836			
		10	0.716			
	As received	11	0.733			
		12	0.689			
		13	0.702			
Paraffin oil test	Simulated wearing treatment	14	0.774			
		15	0.729			
	Machaniaal atropath   Tampayatura	16	3.106			
	Mechanical strength +Temperature conditioned	17	4.528			
	Conditioned	18	3.895			
Flow conditioning: Single filter: 95.0 L/min						



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.ysg.com/en/Terms-and-Conditions.aspx">http://www.ysg.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents at <a href="http://www.ysg.com/en/Terms-and-Conditions.aspx">http://www.ysg.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents as <a href="http://www.ysg.com/en/Terms-and-Conditions.aspx">http://www.ysg.com/en/Terms-and-Conditions.aspx</a> attention is drawn to the imitation of labellity, indemnification and jurisdiction issues defined therein. Any holder of this document says attention of the same of



SL52115283820301TX

Date:July 16,2021

Page 5 of 10

#### Clause 7.10 Compatibility with Skin

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall not be known to be likely to cause irritation or any other adverse effect to health.	No irritation or any other adverse effect to health	Pass

#### Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and shall not be of highly flammable nature	Detail refer to	Dage
When tested, the particle filtering half mask shall not burn or not to continue to burn for more than 5 s after removal from the flame.	Appendix 3	Pass

#### Appendix 3: Summarization of Test Data

			lit۱	

<u>Fiammability</u>		
Condition	Sample No.	Result
		NIL NIL
As received	$D\Gamma C 2 \Gamma$	V CADECEE NILV CADECEE
KESEE V CA	KESzE	V CAKESEE NILV CAKESEE
Temperature conditioned	4	

#### Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1.0 % (by volume)	Detail refer to Appendix 4	Pass

## Appendix 4: Summarization of Test Data

#### Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Resul	Result(%)				
	1	0.4643					
As received	2	0.4654	Mean value:0.46				
	3	0.4602					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sg.com/ar/Terms-and-Conditions.aspx.and. for electronic forces and documents, subject to Terms and Conditions for Electronic Documents at http://www.sg.com/ar/Terms-and-Conditions

中国·上海·徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763

e sgs.china@sgs.com



SL52115283820301TX

Date:July 16,2021

Page 6 of 10

# Clause 7.13 Head Harness

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.	Comply	Pass

#### Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical performance tests.	Comply	Pass

# Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
(a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Not applicable due to No exhalation valve	
(b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Not applicable due to No exhalation valve	ESEE
(c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Not applicable due to No exhalation valve	
(d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s.	Not applicable due to No exhalation valve	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.ags.com/ent/Ferras-and-Conditions.agsx.and">http://www.ags.com/ent/Ferras-and-Conditions.agsx.and</a>, for electronic format documents as titus. The company is the state of the company of the company is the company in the company and the company and

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666 f (86-21) 64958763



SL52115283820301TX

Date:July 16,2021

Page 7 of 10

Clause 7.16 Breathing Resistance (EN 149:2001+A1:2009, Clause 8.9)

	Tes	Results	Comment			
The breathing resistances apply to valved and valveless particle filtering half masks and shall meet the requirements of the following table.						
Classification	Maximu	um permitted resista	ance (mbar)		Datail aufonto	Meet FFP1,
	Inf	nalation	Exhalation		Detail refer to	Meet FFP2,
	30 l/min	95 l/min	160 l/min		Appendix 5	Meet FFP3
FFP1	0.6	2.1	3.0			
FFP2	0.7	2.4	3.0			
FFP3	1.0	3.0	3.0			

#### Appendix 5: Summarization of Test Data

### Breathing resistance (mbar)

	_, , ,		T		1					2					3		
	Flow rate(I/mir		Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
As received	Inhalation	30	0.2	0.2	0.1	0.1	0.1	0.1	0.2	0.1	0.2	0.2	0.2	0.2	0.2	0.1	0.2
DC DC	IIIIIaiauon	95	1.0	0.9	1.0	1.0	0.9	1.0	1.0	1.0	0.9	1.0	1.0	0.9	0.9	1.0	1.0
MOMO	Exhalation	160	1.9	2.0	2.0	2.0	2.0	2.0	2.0	1.9	2.0	2.0	2.0	1.9	1.9	2.0	2.0
	Simulated Flow rate(I/min)		THE PERSON		4	1000	THE AND		100 N	5		ord Tilli	1000	HIII JANE	6	See III	1 200
Simulated			Α	В	С	D	E,	Α	В	С	D	VE	A	В	TC	D	Ε
wearing	Inhalation	30	0.1	0.2	0.2	0.2	0.1	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.2	0.1
treatment		95	1.0	1.0	0.9	1.0	1.0	1.0	0.9	1.0	0.9	0.9	0.9	1.0	0.9	0.9	1.0
	Exhalation	160	2.0	1.9	2.0	2.0	1.9	1.9	1.9	2.0	2.0	2.0	2.0	2.0	2.0	1.9	1.9
					7					8					9		
	Flow rate(I/min)	/min)	Α	В	С	D	E	Α	В	C	D	Ë	Α	В	С	D	Έ
Temperature	Inhalation	30	0.1	0.1	0.2	0.1	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.1	0.1
conditioned	IIIIIaiallOII	95	1.0	0.9	0.9	0.9	0.9	1.0	1.0	1.0	0.9	0.9	1.0	1.0	0.9	0.9	0.9
	Exhalation	160	1.9	1.9	1.9	1.9	2.0	1.9	1.9	2.0	1.9	1.9	1.9	1.9	2.0	2.0	1.9

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 www.sgsgroup.com.cn f (86-21) 64958763 e sgs.china@sgs.com



SL52115283820301TX

Date:July 16,2021

Page 8 of 10

# Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

	Test Requirement	Results	Comment	
Valved particle filt After clogging the FFP1: 4 mbar, FF The exhalation re flow.  Valveless particle After clogging the	eathing resistance ering half masks: inhalation resistances shall not P2: 5 mbar, FFP3: 7 mbar at 98 sistance shall not exceed 3 mb; filtering half masks: inhalation and exhalation resis P2: 4 mbar, FFP3: 5 mbar at 98	Optional for single shift device only	N.A.	
All types (valved a	<u>netration of filter material</u> and valveless) of particle filterin g requirement shall also meet th			
Classificatio	Maximum penetration	n of test aerosol		
n	Sodium chloride test 95 l/min		Optional for single	N.A.
	%	%	shift device only	
FFP1 FFP2	max. 20 6	max. 20 6		
FFP3	1	11		

#### Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured, where possible by hand	No demountable parts	N.A.

Test	Uncertainty
Total inward leakage	3.4%
Penetration of filter material	4.8%
Carbon dioxide content of the inhalation air	3.9%
Breathing resistance (30L/min)	5.9%
Breathing resistance (95L/min)	4.9%
Breathing resistance (160L/min)	4.3%



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.gs.com/en/Terms-and-Conditions.aspx.and">http://www.gs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents as <a href="http://www.gs.com/en/Terms-and-Conditions.aspx.and">http://www.gs.com/en/Terms-and-Conditions.aspx.and</a>, Attention is drawn to the imitation of liability, indemnification and jurisdiction issues defined therein. Any holder of his document is a fitting that the service of the servi

or email: CN.Doccheck@sgs.com | 3"Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 t (86-21) 61402666 f (86-21) 64958763 www.sgsgroup.com.cn

中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763

e sgs.china@sgs.com



SL52115283820301TX

Date:July 16,2021

Page 9 of 10

Sample Photo



V CARESEE V CARESEE V CARESEE V CAI



Seary Active Firms Services

SSSCS Making Technol Services

SS

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.ags.com/ent/Ferras-and-Conditions.agsx.and">http://www.ags.com/ent/Ferras-and-Conditions.agsx.and</a>, for electronic format documents as titus. The company is the state of the company of the company is the company in the company and the company and

3"Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 f (86-21) 64958763



SL52115283820301TX

Date:July 16,2021

Page 10 of 10



\*\*\*End of Report\*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlear, available on request or accessible at http://www.sgs.com/en/irems-and-Conditions.sspx.and, for electronic format documents as things and conditions as the conditions as the conditions as the conditions are considered as the c

3"Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国 - 上海 - 徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 f (86-21) 64958763