

Reference No. : WTX24F06147559L  
Applicant : Shenzhen Auztek Technology Co., Ltd  
Address : Room 2502, Building H, Liuhecheng, Pingshan district,  
518118, Shenzhen, China  
Manufacturer : The same as above  
Address : The same as above  
Product : LED Bulb  
Model No. : See attachment model list  
Technical data : See attachment model list

**Test specification:****EN 62560:2012+A1:2015+A11:2019****EN 62493:2015+A1:2022**

The above product has been tested by us with the listed standards and found in compliance with the European Directive LVD 2014/35/EU. It is possible to use CE marking to demonstrate the compliance with this LVD Directive.

**Lamp****Self-ballasted LED-lamps for general lighting services by voltage > 50 V - Safety specifications****Assessment Of Lighting Equipment Related To Human Exposure To Electromagnetic Fields**

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the above mentioned EU Directive. Other relevant Directives have to be observed.

After preparation of the necessary technical documentation as well as the EU Declaration of Conformity, the CE marking as shown below can be affixed on the equipment under the sole responsibility of the manufacturer.

Manager: **Jerry Mu**

Date: Jul. 10, 2024

The statement is based on a single evaluation of the sample of above mentioned product. It does not imply an assessment of the whole production.

**Waltek Testing Group (Foshan) Co., Ltd.****Hotline: 400-840-2288      E-mail: [info@waltek.com.cn](mailto:info@waltek.com.cn)****[Http://www.waltek.com.cn](http://www.waltek.com.cn)**



# Attachment

## Model list

220-240V~50/60Hz

Reference No.: WTX24F06147559L

Item	Model	Max input current (A)	Rated power (W)	CCT	Lamp cap	Enclosure	Size (Diameter x height mm)
1	8113-PAR16L-X X-8.5W-YY	0.048	8.5	2000-4000 K	GU10	Plastic+Metal	D50x68
2	8113-PAR16L-X X-6.5W-YY	0.038	6.5	2000-4000 K	GU10	Plastic+Metal	D50x68
3	8110-PAR16-X X-6.5W-YY	0.038	6.5	2000-4000 K	GU10	Plastic+Metal	D50x57
4	8110-PAR16-X X-5.3W-YY	0.030	5.3	2000-4000 K	GU10	Plastic+Metal	D50x57
5	8114-PAR16-X X-6.5W-YY	0.038	6.5	2000-4000 K	GU10	Plastic+Metal	D50x57
6	8114-PAR16-X X-5.3W-YY	0.030	5.3	2000-4000 K	GU10	Plastic+Metal	D50x57

Note: "XX" refers to the series of products, could be "PG" or "HO", PG means CRI97, HO means CRI90, "YY" refers to the CCT of products, could be from 2000K to 4000K